

Part No.	Description
MALE ADAPTOR – FEMALE ADAPTOR – A	
75A	3/4" Male Adaptor – 3/4 Female Thread
100A	1" Male Adaptor – 1" Female Thread
150A	1-1/2" Male Adaptor – 1-1/2" Female Thread
200A	2" Male Adaptor – 2" Female Thread
300A	3" Male Adaptor – 3" Female Thread
FEMALE COUPLER – MALE THREAD – B	
75B	3/4" Female Coupler – 3/4" Male Thread
100B	1" Female Coupler – 1" Male Thread
150B	1-1/2" Female Coupler – 1-1/2" Male Thread
200B	2" Female Coupler – 2" Male Thread
300B	3" Male Adaptor – 3" Female Thread
FEMALE COUPLER – HOSE SHANK – C	
75C	3/4" Female Coupler – 19mm Hose Shank
100C	1" Female Coupler – 25mm Hose Shank
150C	1-1/2" Female Coupler – 38mm Hose Shank
200C	2" Female Coupler – 50mm Hose Shank
300C	3" Female Coupler – 75mm Hose Shank
FEMALE COUPLER – FEMALE THREAD – D	
75D	3/4" Female Coupler – 3/4" Female Thread
100D	1" Female Coupler – 1" Female Thread
150D	1-1/2" Female Coupler – 1-1/2" Female Thread
200D	2" Female Coupler – 2" Female Thread
300D	3" Female Coupler – 3" Female Thread
MALE ADAPTOR – HOSE SHANK – E	
75E	3/4" Male Adaptor – 19mm Hose Shank
100E	1" Male Adaptor – 25mm Hose Shank
150E	1-1/2" Male Adaptor – 38mm Hose Shank
200E	2" Male Adaptor – 50mm Hose Shank
300E	3" Male Adaptor – 75mm Hose Shank
MALE ADAPTOR – MALE THREAD – F	
75F	3/4" Male Adaptor – 3/4" Male Thread
100F	1" Male Adaptor – 1" Male Thread
150F	1-1/2" Male Adaptor – 1-1/2" Male Thread
200F	2" Male Adaptor – 2" Male Thread
300F	3" Male Adaptor – 3" Hose Shank
PLUG – G	
75PL	3/4" Plug
100PL	1" Plug
150PL	1-1/2" Plug
200PL	2" Plug
300PL	3" Plug
CAP – H	
75CAP	3/4" Cap
100Cap	1" Cap
150Cap	1-1/2" Cap
200Cap	2" Cap
300Cap	3" Cap

These Camlock fittings are ideal for use on filling pumps and sprayers. Feature quick release stainless steel locking levers, fibreglass reinforced polypropylene body with EPDM gasket.

Maximum working pressure of 9 bar for 3/4" to 2" and 5 bar for 3" models.

